

# XL-9600

## 2D Wireless Barcode Scanner



### Features

- 1 Buttons support 2 million tests
- 2 Support update online, fast after-sales service
- 3 Storage function, 40,000 EAN-13 barcode support
- 4 Cable Anti - interference design, ensure data transmission
- 5 Super decoding ability, good at reading colored, stained and fuzzy code



Logistics Distribution



Warehouse

Parts Instruction

### SUNLUX IOT TECHNOLOGY (GUANGDONG) INC.

Office Add: Room 1201, Building A, No.76 Xinye Road, Huangpu District, Guangzhou, 511356, China  
 Tel: +86-20-32053765 Fax: +86-20-82115390 Website: www.xl-scan.com E-mail: overseas01@xl-scan.cn



# XL-9600

## Technical Parameters



Performance Parameters	
Image Sensor	CMOS
Light Source	White LED(Lighting) Red LED (Aiming)
CPU	32bit ARM
Resolution	640x480 Pixels
Scanning Speed	60 fps
Minimum Resolution	≥3mil
Depth of Field	60-360mm (13mil PCS90%)
Scanning Angle	rotate 360°, inclination 65°, elevation 60°
System Supported	Android/Windows/Linux/IOS
Scan Mode	Manual trigger & Automatic induction
Decoding Capability	1D: Codabar, Code11, Code39, Code32, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Code93, Code128, GS1-128, UPC-A, UPC-E, EAN 8, EAN 13, GS1 DataBar, RSS14, GS1 DataBar Limited, GS1 DataBar Expanded, etc 2D: PDF417, Micro PDF417, QR Code, Micro QR, Data Matrix, Aztec Code
Physical Parameters	
Size	Scanner: L*W*H= 163*68*80(mm) Charging base: L*W*H=15*6*19(mm)
Weight	Scanner:175g
Interface	USB
Charging Way	Micro USB cable charging
Standby Time	6 months(Dormant state)
Continuous Battery Life	16H
Battery	Replaceable & Rechargeable lithium battery, 2600mAh
Receiver Interface	USB
Material	ABS+TPU
Input Voltage	DC 5V
Working Current	250mA
Stand-by Current	<1uA
Indicator	LED indicator light, buzzer
Interface	USB / USB-VCP
Other Parameters	
Communication Methods	2.4G wireless communication, Bluetooth wireless communication
Communication Distance	2.4G mode: 100M (open space) Bluetooth mode: 10M (open space)
Temperature (Operating)	-10°C~50°C
Humidity (Operating)	Relative humidity 5%~95%(no condensation)
Temperature (Storage)	-20°C~60°C
Light Source	0~5,000Lux(fluorescent), 0~100,000Lux(Sunlight)

### SUNLUX IOT TECHNOLOGY (GUANGDONG) INC.

Office Add: Room 1201, Building A, No.76 Xinye Road, Huangpu District, Guangzhou, 511356, China  
Tel: +86-20-32053765 Fax: +86-20-82115390 Website: www.xl-scan.com E-mail: overseas01@xl-scan.cn

