

XL-9620D

2D Wireless Barcode Scanner

New Design Concept
Strong Compatibility
Independent Core Technology



Red LED



ARM



1D/2D



Mobile payment



640x480Pixel



Applications



Features

- Light industrial rugged housing, withstand drop of 1.5m
- 640x480 pixels high level image sensor, easy and quick reading barcodes
- Transmission distance in open space: 2.4G 100m, BT 10m
- Compact size fit for all kinds of applications
- Buzzer and blue LED light indicator, clear scanning feedback

SUNLUX IOT TECHNOLOGY (GUANGDONG) INC.

Office Add: Room 1201, Building A, No.76 Xinye Road, Huangpu District, Guangzhou, 511356, China
Tel: +86-20-32053765 Fax: +86-20-82115390 Website: www.xl-scan.com E-mail: overseas01@xl-scan.cn



XL-9620D

Technical Parameters

Performance Parameters

Light Source	White LED(Lighting) Red LED (Aiming)
CPU	32bit ARM
Scan Mode	Manual trigger & Automatic induction
Image Sensor	CMOS
Coms Resolution	640x480 Pixels
Scanning Speed	60 fps
System Supported	Android/Windows/Linux/IOS
Minimum Resolution	≥3mil
Scanning Angle	Rotate 360°, Inclination 65°, Elevation 60°
Depth Of Field	50~390mm(13mil code39)
Decoding Capability	1D: Codabar, Code11, Code39, Code32, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Code93, Code128, GS1-128, UPC-A, UPC-E, EAN 8, EAN 13, GS1 DataBar(RSS14), GS1 DataBar Limited, GS1 DataBar Expanded, etc 2D: PDF417, Micro PDF417, QR Code, Micro QR, Data Matrix, Aztec Code



Physical Parameters

Size	Scanner: L*W*H= 147.7*90.6*62.8(mm) Receiver: L*W*H=15*6*19(mm)
Weight	Scanner:185g Receiver: 1.6g
Material	ABS+PC
Input Voltage	DC 5V
Working Current	250mA
Stand-by Current	<90mA
Indicator	LED indicator light, buzzer
Interface	USB / USB-VCP
Charging Way	Charging with Type-C cable
Charging Time	4.5H
Standby Time	6 months(Dormant state)
Continuous Battery Life	27H
Battery	Replaceable & Rechargeable lithium battery, 2600mAh
Receiver Interface	USB

Other Parameters

Communication Methods	2.4G wireless communication, Bluetooth wireless communication
Communication Distance	2.4G mode: 100M (open space) Bluetooth mode: 10M (open space)
Humidity (Operating)	Relative humidity 5%~95%(no condensation)
Temperature	-10°C~50°C (Operating), -20°C~60°C (Storage)
Light source	0~5000Lux(fluorescent), 0~100,000Lux(Sunlight)

